



FORCE REQUIRED TO SHIFT	
PRESSURE	SHIFT FORCE
25 PSI	1.60 - 1.65 LBS
50 PSI	2.50 - 2.70 LBS
100 PSI	4.20 - 4.50 LBS
125 PSI	5.40 - 5.60 LBS

FLG	QTY	PART NO	DESCRIPTION
5	1	V-360	KNOB, BLACK (BRASS 1/4-20 INSERT), 1 3/8 DIA, PUSH/PULL
4	1	BBS-1	SPRING - BUTTON BLEEDER, 1/8" NPTF
3	1	V-29	O-RING, 1/8 X1/4 X1/16 BUNA-N 90 D. FOR BUTTON BLEEDER ASSY
2	1	BBSP-1K	PLUNGER, STEEL BUTTON BLEEDER, W/MALE THREADS
1	1	BBB-1	BODY, BRASS BUTTON BLEEDER DOUBLE EX - FIN -

LIMITS ON DIMENSIONS  
UNLESS OTHERWISE SPECIFIED

2-PL DECIMAL ± .01  
3-PL DECIMAL ± .005  
FRACTIONAL ± 1/64  
ANGULAR ± 1/2°



**AAA PRODUCTS INTERNATIONAL**  
7114 Harry Hines Blvd  
Dallas, TX 75235

DRAWN: RMcKenna DATE: 8/26/2011 CHECKED: KWaite DATE: 3/28/2012

SCALE: 2 : 1 SHEET: 1 OF 1 RELEASED: HWomack DATE: 3/28/2012

TITLE: <b>ASSEMBLY - BB-1P, WITH PALM BUTTON, BUTTON BLEEDER</b>	PART NO.: <b>BB-1P</b>	REV.:
---	---------------------------	-------

D:\Engineering\Inventor Files\Internal Drawings\Valves\Button\BB-1P.idw