



FORCE REQUIRED TO SHIFT	
PRESSURE	SHIFT FORCE
25 PSI	1.60 - 1.65 LBS
50 PSI	2.50 - 2.70 LBS
100 PSI	4.20 - 4.50 LBS
125 PSI	5.40 - 5.60 LBS

FLG	QTY	PART NO	DESCRIPTION
4	1	BBSS-1	SPRING - BUTTON BLEEDER, STAINLESS STEEL, 1/8" NPTF
3	1	V-137	O-RING, 1/8 X1/4 X1/16 VITON 90 D. FOR SS BUTTON BLEEDER
2	1	BBP-1SSL	PLUNGER, S/S BUTTON BLEEDER, W/LARGE HEAD
1	1	BBB-1	BODY, BRASS BUTTON BLEEDER DOUBLE EX - FIN -

LIMITS ON DIMENSIONS
UNLESS OTHERWISE SPECIFIED

2-PL DECIMAL ± .01
3-PL DECIMAL ± .005
FRACTIONAL ± 1/64
ANGULAR ± 1/2°



AAA PRODUCTS INTERNATIONAL
7114 Harry Hines Blvd
Dallas, TX 75235

DRAWN: RMcKenna DATE: 8/29/2001 CHECKED: KWaite DATE: 3/28/2012

SCALE: 2 : 1 SHEET: 1 OF 1 RELEASED: HWomack DATE: 3/28/2012

TITLE: ASSEMBLY - BB-1SSL, STAINLES STEEL LARGE BUTTON, BUTTON BLEEDER	PART NO.: BB-1SSL	REV.: A
--	-----------------------------	-------------------

NO.	DATE	REVISION
A	7/12/10	CORRECTED PART CALLOUTS, BBSS-1 WAS BBS-1, V-137 WAS V-29.

